

Safety data sheet

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 PRODUCT IDENTIFIER

Product name

MITOSOL S50

1.2 RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

Relevant identified uses

Solvent, thinner

Uses advised against

No information.

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Manufacturer

MITOL, tovarna lepil, d.o.o., Sežana
Partizanska c. 78
6210 Sežana, Slovenia
+386 5 73 12 300 (8:00-16:00)
lilijana.kocjan@mitol.si

1.4 EMERGENCY TELEPHONE NUMBER

Emergency

112

Manufacturer

+386 5 73 12 300 (8:00-16:00)



<https://my.chemius.net/p/IVdaGr/en/pd/en>

SECTION 2: HAZARDS IDENTIFICATION

2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

Classification according to Regulation (EC) No 1272/2008 (CLP)

Flam. Liq. 3; H226 Flammable liquid and vapour.
Asp. Tox. 1; H304 May be fatal if swallowed and enters airways.
Acute Tox. 4; H312 Harmful in contact with skin.
Skin Irrit. 2; H315 Causes skin irritation.
Eye Irrit. 2; H319 Causes serious eye irritation.
Acute Tox. 4; H332 Harmful if inhaled.
STOT SE 3; H335 May cause respiratory irritation.
STOT RE 2; H373 May cause damage to organs through prolonged or repeated exposure.

2.2 LABEL ELEMENTS

Labelling according to Regulation (EC) No 1272/2008 [CLP]



Signal word: Danger

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P331 Do NOT induce vomiting.
P370 + P378 In case of fire: Use fire extinguishing powder or alcohol resistant foam to extinguish.
P501 Dispose of contents/container in accordance with national regulation.

Contains:

reaction mass of ethylbenzene and m-xylene and p-xylene
xylene



Safety data sheet

2.3 OTHER HAZARDS

No information.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 SUBSTANCES

For mixtures see 3.2.

3.2 MIXTURES

Name	CAS EC Index Reach	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	Notes for substances
reaction mass of ethylbenzene and m-xylene and p-xylene	- 905-562-9 - 01-2119555267-33	≤100	Flam. Liq. 3; H226 / Asp. Tox. 1; H304 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332 STOT SE 3; H335 STOT RE 2; H373		/
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	≤100	Flam. Liq. 3; H226 / Asp. Tox. 1; H304 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332 STOT SE 3; H335 STOT RE 2; H373		C
ethylbenzene	100-41-4 202-849-4 601-023-00-4	≤25	Flam. Liq. 2; H225 / Asp. Tox. 1; H304 Acute Tox. 4; H332 STOT RE 2; H373		/
o-xylene	95-47-6 202-422-2 601-022-00-9	≤13	Flam. Liq. 3; H226 / Acute Tox. 4; H312 Skin Irrit. 2; H315 Acute Tox. 4; H332		C
toluene	108-88-3 203-625-9 601-021-00-3	≤1	Flam. Liq. 2; H225 / Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Repr. 2; H361d STOT RE 2; H373		/

Notes for substances



Safety data sheet

C	<p>Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers.</p> <p>In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.</p>
---	--

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID MEASURES

General notes

Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency. Symptoms of poisoning may even occur after several hours; therefore medical observation is required at least 48 hours after the event.

Following inhalation

Remove patient to fresh air - move out of dangerous area. If victim is not breathing give artificial respiration. In case of difficulty breathing, give oxygen to the victim. If symptoms develop and persist, seek medical attention.

Following skin contact

Immediately remove contaminated clothing. Wash affected skin areas thoroughly with plenty of water and soap. In case of burn rinse with water until the pain ceases. Body hypothermia must be avoided. If symptoms develop and persist, seek medical attention.

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. After 5 minutes of rinsing, remove contact lenses, if present, and continue rinsing. If irritation persists, seek professional medical attention.

Following ingestion

Immediately consult a doctor. Show the physician the safety data sheet or label. Do not induce vomiting! Aspiration hazard if swallowed. Never give anything by mouth to an unconscious person.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Following inhalation

Harmful. Coughing, sneezing, nasal discharge, labored breathing. Intoxication, vertigo, headache, nausea. Prolonged inhalation of vapours can cause lung injury.

Following skin contact

Harmful. Itching, redness, pain. Can cause injuries.

Following eye contact

Redness, tearing, pain.

Following ingestion

Harmful to health. May cause nausea/vomiting and diarrhea.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

No information.

SECTION 5: FIREFIGHTING MEASURES

5.1 EXTINGUISHING MEDIA

Suitable extinguishing media

Carbon dioxide. Dry chemical powder. Water spray. Alcohol resistant foam.

Unsuitable extinguishing media

Full water jet.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Hazardous combustion products

In case of heating harmful vapours/gases can be generated. In the event of fire the following can be generated: carbon monoxide (CO), carbon dioxide (CO₂). Combustion products may include unidentified organic and inorganic compounds.

5.3 ADVICE FOR FIREFIGHTERS

Protective actions

Cool containers at risk with water spray. If possible remove containers from endangered area. Vapours can form explosive mixtures with air.

Special protective equipment for fire-fighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

Additional information

Contaminated firefighting water must be disposed of in accordance with the regulations; do not allow to reach the sewage system.

SECTION 6: ACCIDENTAL RELEASE MEASURES



Safety data sheet

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

For non-emergency personnel

Protective equipment

Use personal protective equipment (Section 8). Avoid contact with the eyes and skin.

Precautionary measures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking! Take precautionary measures against static discharges.

Emergency procedures

Remove all unauthorized persons upwind to a safe distance. Avoid contact with skin and eyes. Do not breathe vapour or mist.

For emergency responders

Use personal protective equipment.

6.2 ENVIRONMENTAL PRECAUTIONS

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

For containment

No information.

For cleaning up

Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Collect in a suitable container and dispose in accordance with the methods under Section 13. Do not absorb spillage with sawdust or other combustible material. In case of major contamination, the contaminated soil layer should be removed. In case of small spillages in closed waters, contain product with floating barriers or other equipment or floating absorbents. The use of dispersants should be advised by an expert.

OTHER INFORMATION

No information.

6.4 REFERENCE TO OTHER SECTIONS

See also sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Protective measures

Measures to prevent fire

Ensure adequate ventilation. Keep away from sources of ignition - no smoking. Use spark-proof tools. Take precautionary measures against static discharges. Vapours and air form explosive mixtures. Ensure proper grounding of the equipment. Take into account existing regulations on the emission of hazardous substances into the environment (par. 12) and explosion limits (par. 9). Use explosively safe equipment (ventilators, lighting, working instruments and devices,...);

Measures to prevent aerosol and dust generation

Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

Measures to protect the environment

No information.

Other measures

No information.

Advice on general occupational hygiene

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin and eyes. Do not breathe vapours/mist. Remove contaminated clothes and wash them before reuse.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Technical measures and storage conditions

Keep in cool and well ventilated area. Protect from open fire, heat and direct sunlight. Keep away from food, drink and animal feeding stuffs. Handle and open the container carefully. Flammable mixtures may be formed in empty containers. Empty containers may still contain explosive vapors and are therefore considered as hazardous waste. Store between: 5 - 40 °C Keep away from oxidising substances. Store in a closed and properly labeled containers away from strong oxidising agents. Keep away from self-igniting materials.

Packaging materials

Store only in original container.

Requirements for storage rooms and vessels

Close opened containers after use. Put the containers upright to prevent from leaking. Do not store in unlabelled containers.

Storage class

No information.

Further information on storage conditions

No information.



Safety data sheet

7.3 SPECIFIC END USE(S)

Recommendations

Do not use compressed air during filling, emptying or handling.

Industrial sector specific solutions

No information.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

Occupational Exposure limit values

Name	mg/m ³	ml/m ³	Short-term value mg/m ³	Short-term value ml/m ³	Remark	Biological Tolerance Values
Xylene, o-,m-,p- or mixed isomers (1330-20-7)	220	50	441	100	Sk, BMGV	650 mmol methyl hippuric acid/mol creatinine in urine - Post shift
Toluene (108-88-3)	191	50	384	100	Sk	/

Information on monitoring procedures

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2021 Workplace exposure. Procedures for the determination of the concentration of chemical agents. Basic performance requirements.

DNEL/DMEL values

For product

No information.

For components

Name	Type	Exposure route	exp. frequency	Remark	value
reaction mass of ethylbenzene and m-xylene and p-xylene	Worker	inhalation	long term systemic effects	/	221 mg/m ³
reaction mass of ethylbenzene and m-xylene and p-xylene	Worker	inhalation	short term systemic effects	/	442 mg/m ³
reaction mass of ethylbenzene and m-xylene and p-xylene	Worker	dermal	short term systemic effects	/	3182 mg/kg bw/day
reaction mass of ethylbenzene and m-xylene and p-xylene	Consumer	inhalation	long term systemic effects	/	65.3 mg/m ³
reaction mass of ethylbenzene and m-xylene and p-xylene	Consumer	inhalation	short term systemic effects	/	260 mg/m ³
reaction mass of ethylbenzene and m-xylene and p-xylene	Consumer	dermal	long term systemic effects	/	1872



Safety data sheet

Name	Type	Exposure route	exp. frequency	Remark	value
reaction mass of ethylbenzene and m-xylene and p-xylene	Consumer	oral	long term systemic effects	/	12.5
xylene	Worker	inhalation	short term systemic effects	/	289 mg/m ³
xylene	Worker	inhalation	short term local effects	/	289 mg/m ³
xylene	Worker	dermal	long term systemic effects	/	180 mg/kg
xylene	Worker	inhalation	long term systemic effects	/	77 mg/m ³
xylene	Consumer	inhalation	short term systemic effects	/	174 mg/m ³
xylene	Consumer	inhalation	short term local effects	/	174 mg/m ³
xylene	Consumer	dermal	long term systemic effects	/	108 mg/kg
xylene	Consumer	inhalation	long term systemic effects	/	14.8 mg/m ³
ethylbenzene	Consumer	inhalation	long term systemic effects	/	14.8 mg/m ³
ethylbenzene	Consumer	oral	long term systemic effects	/	1.6 mg/kg
ethylbenzene	Worker	dermal	long term systemic effects	/	180 mg/kg
ethylbenzene	Worker	inhalation	long term systemic effects	/	77 mg/m ³
ethylbenzene	Worker	inhalation	short term systemic effects	/	289 mg/m ³
ethylbenzene	Consumer	dermal	long term systemic effects	/	108 mg/kg
ethylbenzene	Consumer	inhalation	short term systemic effects	/	174 mg/m ³
ethylbenzene	Consumer	inhalation	short term local effects	/	174 mg/m ³

PNEC values

For product

No information.

For components

Name	Exposure route	Remark	value
reaction mass of ethylbenzene and m-xylene and p-xylene	fresh water	/	0.25 mg/L
reaction mass of ethylbenzene and m-xylene and p-xylene	marine water	/	0.25 mg/L
reaction mass of ethylbenzene and m-xylene and p-xylene	fresh water sediment	/	14.33 mg/kg



Safety data sheet

Name	Exposure route	Remark	value
reaction mass of ethylbenzene and m-xylene and p-xylene	soil	/	2.41 mg/kg
xylene	fresh water	/	0.327 mg/L
xylene	marine water	/	0.327 mg/L
xylene	water, intermittent release	/	0.327 mg/L
xylene	water treatment plant	/	6.58 mg/L
xylene	fresh water sediment	/	12.46 mg/kg
xylene	marine water sediment	/	12.46 mg/kg
xylene	soil	/	2.31 mg/kg
ethylbenzene	soil	/	2.68 mg/kg
ethylbenzene	fresh water	/	0.1 mg/L
ethylbenzene	marine water	/	0.01 mg/L
ethylbenzene	water, intermittent release	/	0.1 mg/L
ethylbenzene	fresh water sediment	/	13.7 mg/kg
ethylbenzene	water treatment plant	/	9.6 mg/L

8.2 EXPOSURE CONTROLS

Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices – wash hands at breaks and when done working with material. Keep away from direct sun-light or other heat sources and sources of ignition. Avoid contact with eyes and skin. Do not breathe vapours/aerosols. Do not eat, drink or smoke while working.

Structural measures to prevent exposure

No information.

Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse. Keep eyewash bottles or personal eyewash units and emergency showers available.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration.

Personal protective equipment

Eye and face protection

Safety glasses with side protection (EN 166).

Hand protection

Protective gloves (EN 374). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Appropriate materials

Material	Thickness	Penetration Time	Remark
Viton (fluorinated rubber)	0.4 mm	8 h	/

Skin protection

Protective antistatic clothing EN 1149 (1:2006, 2:1998 and 3:2004, 5:2008), protective antistatic shoes (EN 20345:2012). At higher exposures wear chemical-resistant clothing (EN 13034) and boots, natural rubber (EN 20345). Choose body protection according to the activity and possible exposure.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory protection. Protective masks (EN 136) or half masks (EN 140) with filter A (EN 14387).

Thermal hazards

No information.

Environmental exposure controls

Substance/mixture related measures to prevent exposure

No information.

Instruction measures to prevent exposure

No information.

Organisational measures to prevent exposure



Safety data sheet

No information.

Technical measures to prevent exposure

No information.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Physical state

liquid

Colour

colourless

Odour

slightly aromatic

Important health, safety and environmental information

Odour threshold	No information.
pH	No information.
Melting point/Freezing point	-25 °C
Initial boiling point/boiling range	137 – 143 °C
Flash point	25 °C
Evaporation rate	No information.
Flammability (solid, gas)	No information.
Explosion limits (vol%)	1 – 7 vol %
Vapour pressure	8 hPa at 20 °C
Vapour density	No information.
Density / weight	Density: 0.87 g/cm ³ at 20 °C
Solubility	Water: 9 g/l at 25 °C
Partition coefficient	Octanol-water (log Pow): 2.77 – 3.15
Auto-ignition temperature	ca. 460 °C
Decomposition temperature	No information.
Viscosity	Dynamic: 0.61 mPas at 20 °C
Explosive properties	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
Oxidising properties	No information.

9.2 OTHER INFORMATION

No information.

SECTION 10: STABILITY AND REACTIVITY

10.1 REACTIVITY

No information.

10.2 CHEMICAL STABILITY

Product is stable under normal conditions of use, recommended handling and storage conditions.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS

No information.

10.4 CONDITIONS TO AVOID

Protect from heat, direct sunlight, open fire, sparks. Protect against electrostatic charge build-up.

10.5 INCOMPATIBLE MATERIALS

Strong acids. Strong oxidising agents.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released. Carbon dioxide; Carbon monoxide.



Safety data sheet

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

(a) Acute toxicity

For product

Exposure route	Type	Species	Time	value	Method	Remark
inhalation (vapours)	ATE	/	/	11 mg/l	/	calculated value
dermal	ATE	/	/	1100 mg/kg	/	calculated value

For components

Name	Exposure route	Type	Species	Time	value	Method	Remark
xylene	oral	LD ₅₀	/	/	2000 - 5000 mg/kg	/	/
xylene	inhalation	LC ₅₀	/	/	10 - 20 mg/l	/	/

Additional information

Harmful if inhaled. Harmful in contact with skin.

(b) Skin corrosion/irritation

No information.

Additional information

Causes skin irritation.

(c) Serious eye damage/irritation

No information.

Additional information

Causes serious eye irritation.

(d) Respiratory or skin sensitisation

No information.

Additional information

The product is not classified as sensitising.

(e) (Germ cell) mutagenicity

No information.

(f) Carcinogenicity

No information.

(g) Reproductive toxicity

No information.

Summary of evaluation of the CMR properties

The product is not classified as carcinogenic, mutagenic or toxic for reproduction.

(h) STOT-single exposure

No information.

Additional information

STOT - single exposure: May cause respiratory irritation.

(i) STOT-repeated exposure

No information.

Additional information

May cause damage to organs through prolonged or repeated exposure.

(j) Aspiration hazard

No information.

Additional information

May be fatal if swallowed and enters airways.

SECTION 12: ECOLOGICAL INFORMATION



Safety data sheet

12.1 TOXICITY

Acute (short-term) toxicity

For components

Name	Type	value	Exposure time	Species	organism	Method	Remark
reaction mass of ethylbenzene and m-xylene and p-xylene	LC ₅₀	> 1.3 mg/L	/	fish	/	/	/
xylene	LC ₅₀	26.7 mg/L	96 h	fish	<i>Pimephales promelas</i>	/	/
xylene	LC ₅₀	16.9 mg/L	96 h	fish	<i>Carassius auratus</i>	/	/
xylene	LC ₅₀	20.9 mg/L	96 h	fish	<i>Lepomis macrochirus</i>	/	/
xylene	LC ₅₀	34.7 mg/L	96 h	fish	<i>Poecilia reticulata</i>	/	/
xylene	EC ₅₀	1 mg/L	48 h	crustacea	<i>Daphnia magna</i>	/	/
xylene	IC ₅₀	2.2 mg/L	72 h	algae	/	/	/

Chronic (long-term) toxicity

For components

Name	Type	value	Exposure time	Species	organism	Method	Remark
xylene	NOEC	> 1.3 mg/l	56 days	fish	/	/	/
xylene	NOEC	0.96 mg/l	7 days	Magna Daphnia	/	/	/

12.2 PERSISTENCE AND DEGRADABILITY

Abiotic degradation, physical- and photo-chemical elimination

No information.

Biodegradation

For components

Name	Type	Rate	Time	Evaluation	Method	Remark
reaction mass of ethylbenzene and m-xylene and p-xylene	BOD	57 - 80 g/g	/	/	/	/

Additional information

Preparation with easily biodegradable substances.

12.3 BIOACCUMULATIVE POTENTIAL

Partition coefficient

For product

Media	value	Temperature °C	pH	Concentration	Method
Octanol-water (log Pow)	2.77 - 3.15	/	/	/	/

For components



Safety data sheet

Name	Media	value	Temperature °C	pH	Concentration	Method
xylene	Octanol-water (log Pow)	3.12 - 3.2	/	/	/	/

Bioconcentration factor (BCF)

For components

Name	Species	organism	value	Duration	Evaluation	Method	Remark
xylene	BCF	/	25.9	/	/	/	/

12.4 MOBILITY IN SOIL

Known or predicted distribution to environmental compartments

No information.

Surface tension

No information.

Adsorption/Desorption

No information.

12.5 RESULTS OF PBT AND VPVB ASSESSMENT

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6 OTHER ADVERSE EFFECTS

No information.

12.7 ADDITIONAL INFORMATION

For product

Do not allow to reach ground water, water courses or sewage system.

For components

reaction mass of ethylbenzene and m-xylene and p-xylene
Bioaccumulation is not expected.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS

Product / Packaging disposal

Waste chemical

Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste. Reuse or recycle, if possible. Do not allow product to reach drains/sewage systems.

Waste codes / waste designations according to LoW

No information.

Packaging

Deliver completely emptied containers to approved waste disposal authorities. Cleaned uncontaminated packaging may be taken for recycling. Uncleaned containers should not be perforated, cut or welded.

Waste codes / waste designations according to LoW

No information.

Waste treatment-relevant information

No information.

Sewage disposal-relevant information

No information.

Other disposal recommendations





No information.

SECTION 14: TRANSPORT INFORMATION

ADR/RID	IMDG	IATA	ADN
14.1 UN number			
UN 1307	UN 1307	UN 1307	UN 1307
14.2 UN proper shipping name			



Safety data sheet

ADR/RID	IMDG	IATA	ADN
XYLENES	XYLENES	XYLENES	XYLENES
14.3 Transport hazard class(es)			
3	3	3	3
			
14.4 Packing group			
III	III	III	III
14.5 Environmental hazards			
NO	NO	NO	NO
14.6 Special precautions for user			
Limited quantities 5 L Packing Instructions P001, IBC03, LP01, R001 Transport category 3 Tunnel restriction code (D/E)	Limited quantities 5 L EmS F-E, S-D Flash point °C	Limited Quantity, Packing Instructions (Ltd Qty, Pkg Inst) Y344 Limited Quantity, Maximum Net Quantity/Package (Ltd Qty, Max Net Qty/Pkg) 10 L Packing Instructions (Pkg Inst) 355 Maximum Net Quantity/Package (Max Net Qty/Pkg) 25 L Special provisions A3	Limited quantities 5 L
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code			
Goods may not be carried in bulk in bulk containers, containers or vehicles.	Goods may not be carried in bulk in bulk containers, containers or vehicles.	Not given/not applicable	Not given/not applicable

SECTION 15: REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)

- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

not applicable

Regulation EC 648/2004 on detergents

No information.

Special instructions

Seveso P5c: FLAMMABLE LIQUIDS. Regulation (EC) No. 1907/2006 (REACH) Annex XVII - Terms of restriction: 3, 40. Regulation (EC) No. 1907/2006 (REACH) Annex XVII - Terms of restriction: 48 toluene - Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.



Safety data sheet

15.2 CHEMICAL SAFETY ASSESSMENT

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION

Indication of changes

No information.

Key literature references and sources for data

No information.

Abbreviations and acronyms



Safety data sheet

ATE - Acute Toxicity Estimate
 ADR - Agreement concerning the International Carriage of Dangerous Goods by Road
 ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 CEN - European Committee for Standardisation
 C&L - Classification and Labelling
 CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
 CAS# - Chemical Abstracts Service number
 CMR - Carcinogen, Mutagen, or Reproductive Toxicant
 CSA - Chemical Safety Assessment
 CSR - Chemical Safety Report
 DMEL - Derived Minimal Effect Level
 DNEL - Derived No Effect Level
 DPD - Dangerous Preparations Directive 1999/45/EC
 DSD - Dangerous Substances Directive 67/548/EEC
 DU - Downstream User
 EC - European Community
 ECHA - European Chemicals Agency
 EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)
 EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)
 EEC - European Economic Community
 EINECS - European Inventory of Existing Commercial Substances
 ELINCS - European List of notified Chemical Substances
 EN - European Standard
 EQS - Environmental Quality Standard
 EU - European Union
 Euphrac - European Phrase Catalogue
 EWC - European Waste Catalogue (replaced by LoW – see below)
 GES - Generic Exposure Scenario
 GHS - Globally Harmonized System
 IATA - International Air Transport Association
 ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air
 IMDG - International Maritime Dangerous Goods
 IMSBC - International Maritime Solid Bulk Cargoes
 IT - Information Technology
 IUCLID - International Uniform Chemical Information Database
 IUPAC - International Union for Pure Applied Chemistry
 JRC - Joint Research Centre
 Kow - octanol-water partition coefficient
 LC50 - Lethal Concentration to 50 % of a test population
 LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose)
 LE - Legal Entity
 LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
 LR - Lead Registrant
 M/I - Manufacturer / Importer
 MS - Member States
 MSDS - Material Safety Data Sheet
 OC - Operational Conditions
 OECD - Organization for Economic Co-operation and Development
 OEL - Occupational Exposure Limit
 OJ - Official Journal
 OR - Only Representative
 OSHA - European Agency for Safety and Health at work
 PBT - Persistent, Bioaccumulative and Toxic substance
 PEC - Predicted Effect Concentration
 PNEC(s) - Predicted No Effect Concentration(s)
 PPE - Personal Protection Equipment
 (Q)SAR - Qualitative Structure Activity Relationship
 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
 RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
 RIP - REACH Implementation Project
 RMM - Risk Management Measure
 SCBA - Self-Contained Breathing Apparatus
 SDS - Safety data sheet
 SIEF - Substance Information Exchange Forum
 SME - Small and Medium sized Enterprises
 STOT - Specific Target Organ Toxicity
 (STOT) RE - Repeated Exposure
 (STOT) SE - Single Exposure
 SVHC - Substances of Very High Concern
 UN - United Nations
 vPvB - Very Persistent and Very Bioaccumulative

List of relevant H phrases



Safety data sheet

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.